

PM-tank 130L[®]

Professional break tank

TECHNICAL CHARACTERISTICS

- Useful water storage: 130 liters
- Installation : flat floor
- The tank is designed for 1 submersible 5" waterpumps or 1 selfpriming centrifugal waterpump
- According EN 1717 specifications (CAT 5) – Belgaqua approved
- Integrated overflow DN75
- Compact
- The tank is designed for narrow passages & spiral staircases
- On the bottom of the tank, on the front side, there is a 1" brass connection for drainage or junction of PM130 tanks
- The PM tank 130/1 is supplied with 1 float 3/4" AUK Muller DN17
- The PM tank 130/2 is supplied with 2 float 3/4" AUK Muller DN17 and a manifold in 3/4"
- 1 removable lid for cleaning
- Color: black
- Material: recyclable polyethylene WRAS compliant
- Dimensions: 600*350*980 mm (L*D*H)



3/4 VISTA



FRONT



Indirizzo / Address

Via Palermo n°30/3 20053 – Rodano (MI) – Italia

Tel. / Phone

+39 379 1305072

Email

info@pmtechconsulting.it

Website

www.pmtechproducts.com

www.pmtechconsulting.it

P.Iva / VAT: IT13416610965



Choose the right tank

PM BREAK 130



- Supplied with 1 float 3/4- DN17 or
- Supplied with 2 float 3/4- DN17 and manifold in 3/4"

Ideal for:

- ✓ Apartment buildings
- ✓ Hotel
- ✓ Schools
- ✓ Commercial buildings

